

## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
29 January 2004 (29.01.2004)

PCT

(10) International Publication Number  
**WO 2004/010460 A2**

(51) International Patent Classification<sup>7</sup>: **H01J 61/00**

(21) International Application Number:  
PCT/JP2003/009234

(22) International Filing Date: 22 July 2003 (22.07.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
2002-212911 22 July 2002 (22.07.2002) JP

(71) Applicant (for all designated States except US): MAT-  
SUSHITA ELECTRIC INDUSTRIAL CO., LTD.  
[JP/JP]; 1006, Oazakadoma, Kadoma-shi, Osaka 571-8501  
(JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): NAKANISHI,

Akiko [JP/JP]; 7-85, Ikagakitamachi, Hirakata-shi, Osaka  
573-0036 (JP). KAKUNO, Yoshinori [JP/JP]; 21-10,  
Kisabe 4-chome, Katano-shi, Osaka 576-0052 (JP).  
IIDA, Shiro [JP/JP]; 1-53, Misasagihirabayashicho, Ya-  
mashina-ku, Kyoto-shi, Kyoto 607-8406 (JP). ITAYA,  
Kenji [JP/JP]; 1-10-18, Fukazawacho, Takatsuki-shi,  
Osaka 569-0035 (JP).

(74) Agent: NAKAJIMA, Shiro; 6F, Yodogawa 5-Bankan,  
2-1, Toyosaki 3-chome, Kita-ku, Osaka-shi, Osaka  
531-0072 (JP).


(81) Designated States (national): CN, ID, US.

## Published:

— without international search report and to be republished  
upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.

(54) Title: LOW-PRESSURE MERCURY LAMP AND METHOD FOR ASSEMBLING THE SAME



(57) **Abstract:** An arc tube is formed by a glass tube that is turned at a substantially middle thereof and wound around a spiral axis from the middle, to have a double-spiral structure. End portions of the arc tube are wound around the spiral axis. A holder has insertion openings formed therein in such shapes that correspond to shapes of the ends of the arc tube. The insertion openings allow the ends of the arc tube to be inserted along a bottom wall of the holder. The holder also includes guide grooves provided in the areas before the insertion openings in the spiral direction of the ends of the arc tube. The guide grooves allow the end portions of the arc tube to come in contact, and when the arc tube is rotated around the axis, guide the ends of the arc tube to the insertion openings.